



- Print, Copy and Scan on the go!
- Weighs only 2.6 lbs.
- Small enough to fit in your briefcase, backpack or purse

Printing on the go just got practical!

Primera Trio is the world's smallest and lightest all-in-one printer, copier and scanner. Use it on the road – whether you're a business traveler, service technician, insurance agent or more – or in tight spaces like dorm rooms, home offices, small apartments and retail counters.

TECHNICAL SPECIFICATIONS

| All-in-One Functions | Print, Scan, Copy |
|---|--|
| Print Speed ¹ | Draft, Letter: 3.1 ppm black, 2.4 ppm color ISO Speeds: Up to 2.4 ppm black, Up to 1.7 ppm color |
| Print Resolution | Up to 4800 dpi |
| Print Technology | Thermal Inkjet |
| Ink Types | Dye-based color and black |
| Borderless Printing | Yes; up to 4x6-in, A6, up to 5-in wide |
| Copy Speed | ISO Speeds: Up to 1.7 ppm black, Up to 1.1 ppm color |
| Copy Resolution | Up to 600 x 600 dpi color and black |
| Scan File Format | Scan file types supported by software: Bitmap (.bmp), JPEG (.jpg PDF (.pdf), PNG (.png), TIFF (.tif), GIF (.gif) |
| Scan Speed | Up to 1.4 ppm (300 dpi, b&w); Up to 1.6 ppm (300 dpi, color) |
| Scan Resolution | Hardware: Up to 600 x 600 dpi Optical: Up to 600 dpi |
| Scan Size Maximum | Up to 8.5x14-in (216 x 356 mm) |
| Bit Depth/Grayscale Levels | 24-bit/256 |
| Standard Connectivity | USB 1.1 (2.0/3.0 compatible) |
| Media Sizes Supported | Letter, legal, A4, A5, A6, 4x6-in photo, U.S. #10 envelope, Hagaki, custom |
| Scanner Capacity | One (sheet, receipt, business card, etc.) |
| Paper Handling | Up to 10 sheets input tray. One sheet input slot on the back for feeding and printing onto light cardstocks and photo paper. |
| Custom Media Sizes | 3x3-in to 8.5x14-in (76.2 x 101.6 mm to 215.9 x 355.6 mm) |
| Compatible Operating Systems | Microsoft® Windows 7, Windows 8, Windows Vista™ (x32 and x64 Mac OS X v 10.6 or higher |
| Minimum System Requirements (Windows®) | Windows Vista™, 7, 8, 8.1 with latest service packs Intel® Celeron® processors or faster (or equivalent) 2 GB RAM 1 GB hard drive space CD/DVD drive if installing software from disc USB 1.1 or higher |
| Minimum System Requirements (Mac*) | OS X v 1.6 or higher 2 GB RAM 1 GB hard drive space CD/DVD drive if installing software from disc USB 1.1 or higher |
| Product Dimensions | W x D x H: 11.4 x 6.5 x 1.8 in (290 x 165 x 46 mm) |
| Product Weight | With no battery: 2.6 lbs (1.2 kg) With battery: 2.8 lbs (1.3 kg) |
| Power | Power supply type: external universal power adapter Input voltage: 100 - 240 VAC Output voltage: 7.5 VDC @ 3.2A |
| Warranty | One-year parts and labor including one year of phone, chat and email support |
| Extended Warranties | Two-year NBD exchange with Level 2 Tech Support Three-year NBD exchange with Level 2 Tech Support |
| What's in the Box | Primera Trio Printer, Primera 31020 color ink cartridge, CD with printer and scanner drivers, application software and user documentation, AC adapter with power cord and plug adapter for EU, AP, UK, 3-foot micro-USB to USB cable, scanner calibration sheet, Quick Reference Guide |
| Accessories | Snap-on cover in clear-coated blue, white, pink or matte silver (black is standard) Lithium-ion battery (Up to 350 pages) 12v vehicle adapter Vehicle mounting kit: includes black painted metal bracket, mountis screws and 12v vehicle power adapter cable and plug 4x6-in photo paper Laptop bag Neoprene zippered sleeve Extended warranty |
| Replacement Ink Cartridges ² | Primera 53335 High-Yield Color Cartridge (580 pages, draft), (260 pages, ISO) ² Primera 53336 High-Yield Black Cartridge (495 pages, draft), (185 pages, ISO) ² Primera 31020 Standard Yield Color Cartridge (175 pages, draft), (70 pages, ISO) Primera 31021 Standard Yield Black Cartridge (360 pages, draft), (135 pages, ISO) |



Express yourself with optional blue, pink, white or silver snap-on covers.



Equip your entire field sales and support teams with Primera Trio!

¹Either after first page or first set of ISO test pages using ISO/24734 ²Replacement cartridge yields are based on ISO/IEC 24711 tests in default mode printing continually.

Specifications are subject to change without notice.