

Stackable Thermal Printer

Technical Specs

Dimensions

- Height: 167 mm (6.6")
- Width: 148 mm (5.8")
- Length: 245 mm (9.6")
- Weight: Approx 3 Kg (6.6 lbs)

Print Method: Direct Thermal

Resolution: 203×203 DPI

Print Width: 80 mm (Max)

Print speed: 250mm/s (Max)

Cutter: Moveable blade, full or partial cut.

Paper:

- **type:** Continuous paper, Marked paper
- **thickness:** 0.06 mm~0.10 mm thermal paper
- **roll width:** 57.5/80/82.5mm
- **roll OD:** 83 mm (max)
- **cut:** Full cut, Partial cut

Interface: USB (default), Ethernet (optional)

Drivers:

- Windows drivers (Win2000/XP/Vista/Win7/Win8/Win10/Win11)
- OPOS
- Linux CUPS
- MAC

Certifications:

- UL / FCC / CB / CE
- Electronics and mechanics following European RoHS and WEEE Directives

Power Supply:

- Integrated Switching Power Supply

Your branches can now benefit from the capabilities of Panini's Stackable Thermal Printer, a reliable and efficient peripheral designed to fit within the compact footprint of the EverneXt scanner, saving you precious space and allowing a print speed up to 250 mm/s.

The printer is easy to open with one hand, it has adjustable paper near-end sensor and is suitable for standard size thermal paper rolls (80mm diameter).

It is also cost effective, allowing to avoid ink cartridges expenses and their related replacement process.

