

# Introducing the Sahara NetSlate® a230T

The lower cost 12.1-inch touch screen Tablet PC designed specifically for business applications.



For added value and convenience, the new **Sahara NetSlate® a230T** Tablet PC is fully compatible with all accessories and peripherals created for the **Sahara Slate PC® i400** series of slate-style Tablet PCs.

Designed for enterprise use, the **Sahara NetSlate® a230T** slate-style Tablet PC, powered by the Intel® Atom™ N270 ULV processor, is the networked touch screen computer well suited for client/server business applications. Its sleek lightweight design, resistive touch screen and versatile form factor, make the Sahara NetSlate an ideal component for both mobile and in-wall touch screen applications such as systems control and self-service kiosks.

The **Sahara NetSlate® a230T** features a full 12.1-inch wide-view TFT XGA LCD with resistive touch screen, dual channel Intel® WiFi 802.11a/b/g/n networking, optional 3G/3.5G built-in WWAN module, Bluetooth® 2.1+EDR and is available with your choice of Windows® 7 Professional, Windows® Embedded or openSUSE™ Linux.



## Hardware Specifications

---

|                    |   |
|--------------------|---|
| <b>Processor:</b>  | Intel® Atom™ N270 (512K L2 cache, 1.60 GHz, 533 MHz FSB)<br>Intel's 45nm Hi-K metal gate silicon technology (2.5W max TDP)<br>Enhanced Intel® SpeedStep® Technology<br>SSE2 and SSE3 instruction set support for increased video decoding<br>Supports C4 power state (Deeper Sleep) for extended battery life     |
| <b>Chipsets:</b>   | Mobile Intel® 945GSE Express (Northbridge) with<br>82801GBM I/O Controller Hub (ICH7-M Southbridge)<br>Direct Media Interface with 10 Gb/s each direction, full duplex  |
| <b>Memory:</b>     | 2x DDR2 533/400 MHz 200 pin SODIMM slots, 1.0 GB standard<br>Single 64-bit wide channel, configurations up to 2.0 GB  |
| <b>Battery:</b>    | 6-Cell Lithium Ion Smart Battery Pack (3,800 mAh @ 11.1 V, 42W/hr)<br>Over Charge Protection, Over Discharge Protection, Over Current<br>and Output Short Protection, Over Thermal Protection<br>Compatible with Sahara Slate PC® Extended Life Battery   |
| <b>Hard Drive:</b> | 2.5" format, 9mm height, configurations from 120GB<br>Ultra DMA SATA 1.5Gbs   |
| <b>Input:</b>      | 12.1" Wide-View TFT XGA (1024x768) LCD display<br>Passive Resistive Touch Screen with PenMount Gestures†  |
| <b>Video:</b>      | Integrated Intel® GMA 950 PCI Express, 3.5 Gen graphics engine<br>250MHz core render clock and 200MHz core display clock<br>Dynamic Video Memory Technology 3.0<br>Up to 224 MB shared video RAM available to Windows®<br>Microsoft® DirectX® 9.1 support   |
| <b>Audio:</b>      | Integrated Intel® HD Audio (ICH7-M)<br>AC'97 Compatible, ALC262-VC2-GR HD Codec, 32-bit/192KHz<br>Built-in 1.5W Stereo Speakers and Dual Digital Microphone Array<br>3.5mm Headphone & Microphone Plug & Play Jacks   |
| <b>Wireless:</b>   | Intel® WiFi Link 5100 Series, integrated half mini card<br>802.11a/b/g/n Dual Channel Networking with Power ON/OFF switch<br>Support for Cisco Compatible Extensions v4 (CKM/CAC/U-APSD/VM)<br>Bluetooth® 2.1+EDR built-in module with Power ON/OFF button<br>Sierra Wireless 3G/3.5G WWAN Data Module (optional) |
| <b>Security:</b>   | Infineon Single Chip Trusted Platform Module (TPM)<br>Trusted Group Computing (TCG) v1.1B / v1.2 compliant<br>Kensington compatible locking port  |
| <b>I/O Ports:</b>  | 1x DC-In, 2x 4-pin USB 2.0, 1x Headphone, 1x Stereo Microphone<br>1x Docking Cradle Connector (dock adds VGA, 4x USB 2.0,<br>RJ45 10/100 Ethernet, IEEE1394a (6-pin), and DC Power pass-thru.   |

## Software Specifications

---

|                          |  |
|--------------------------|--|
| <b>Operating System:</b> | Microsoft® Windows® 7 Professional<br>Microsoft® Windows® Embedded (Special Order)<br>openSUSE™ Linux 11 |
| <b>Applications:</b>     | Adobe Acrobat Reader 9   |

## Accessories

---

|                  |  |
|------------------|--|
| <b>Included:</b> | Standard Lithium-Ion Battery<br>AC Adapter with Power Cord Set<br>Neoprene Slip Case & Presentation Stand<br>Quick Start Guide & Digital User's Guide<br>System Restore DVD <sup>1</sup><br>1 Year Limited Warranty, Parts & Labor   |
| <b>Optional:</b> | <i>Compatible with accessories for i400 series including:</i><br>Docking Cradle with additional I/O Ports<br>Extended Life Battery (for up to 8 hours of use)<br>External Optical Drive (CD, DVD or Combo)<br>Folding USB Keyboard<br>Airplane/Car Charger<br>Bump Cases, Screen Protectors and more.<br>2 Year and 3 Year Extended Warranties |

## Physical Characteristics

---

|                          |  |
|--------------------------|--|
| <b>Weight:</b>           | 1.62 kg (3.57 lbs.) with standard battery pack   |
| <b>Measurements:</b>     | 300 mm x 220 mm x 26 mm<br>(11.81 in x 8.66 in x 1.02 in)  |
| <b>LED Indicators:</b>   | Power (ON: blue, Standby: blinking)<br>Battery (Charging: amber, Low: amber blinking<br>Fully charged with DC connected: green,<br>Fully charged without DC connected: OFF)<br>Hard Drive (Activity: blue blinking)<br>Wireless (WiFi only ON: blue, 3G only ON: Amber,<br>WiFi & 3G both ON: Blue+Amber, OFF: OFF)<br>Bluetooth® (ON: blue, OFF: OFF) |
| <b>Control Switches:</b> | System Power/Stand-by, Bluetooth® transmitter,<br>Wireless Networking transmitter  |
| <b>Function Buttons:</b> | <b>(L):</b> SAS, Screen Rotation, Volume Up/Down<br><b>(R):</b> WiFi/3G mode(s), 3x User Programmable  |
| <b>Mounting:</b>         | VESA MIS-D, 75/100, C (via optional mounting<br>plate or docking cradle)   |
| <b>Temperature:</b>      | Operation: +5°C to +35°C (41°F ~ 95°F)<br>Storage: -20°C to +65°C (4°F ~ 149°F)  |
| <b>Humidity:</b>         | Operation: 20% to 80% (w/o condensation)<br>Storage: 8% to 90% (w/o condensation)  |



2832 Columbia Street, Torrance, California 90503  
310 782 1201 tel 310 782 1205 fax [www.tabletkiosk.com](http://www.tabletkiosk.com)